

SPECTRA PRECISION®

EPOCH® 35 GNSS SYSTEM

SPECSHEET

GENERAL

When connected to the data collector:

- GPS & GLONASS (GNSS) RTK dual frequency with centimeter accuracy
- Ergonomic, light weight and compact design
- Integrated Wireless Bluetooth® 2.0 technology
- Application programs, job, and data management
- Access Network RTK with GPRS

TECHNICAL SPECIFICATIONS

Static GNSS surveying¹

Horizontal ±5 mm +0.5 ppm RMS
 Vertical ±5 mm +1 ppm RMS

Real-Time surveying¹

Horizontal ±10 mm + 1 ppm RMS
 Vertical ±20 mm + 1 ppm RMS
 Initialization Automatic OTF (on-the-fly) while moving
 Initialization time Typically <30 seconds
 Start-up <60 seconds from power on to positioning
 <30 seconds with recent ephemeris

Code differential GPS positioning¹

WAAS/EGNOS differential positioning accuracy... Typically <5 m 3DRMS²

Measurements

- Low elevation satellite tracking technology
- 14 L1, 14 L2 GPS, 12 L1, 12 L2 GLONASS, 2 SBAS, WAAS/EGNOS
- 72 channels
- NMEA-0183: L2/L2C, AVR, GSV, HDT, VGK, VHD, ROT, GSK, GGA, GSA, ZDA, VTG, GST, PJT, and PJK
- 5 Hz position rate

Physical

Dimensions (WxH x D)
 GPS receiver 19.0 cm x 9.76 cm x 20.0 cm
 (7.48 in x 3.8 in x 7.87 in)

Weight

Base 1.0 kg (2.2 lb)
 Rover 1.1 kg (2.4 lb), internal radio, UHF antenna

Ports

I/O Two 7-pin Lemo, RS-232
 Data Link antenna TNC (Rover only)
 Storage SD Card Slot 512MB/1GB⁴

ENVIRONMENTAL

Operating temperature -20 °C to +65 °C (-4 °F to +149 °F)
 Storage temperature -40 °C to +75 °C (-40 °F to +167 °F)
 Humidity 95%, condensing
 Water/Dust IP64
 Shock and vibration: Tested and meets the following environmental standards:
 Shock UNE EN 60068-2-27:1993
 Vibration MIL-STD-810F Fig 514.5C-1

ELECTRICAL

- Power 10 V DC to 15 V DC external power input with over-voltage protection on Port 1 and Port 2 (7-pin)
- Rechargeable, 7.4 V 2400 mAh Li-Ion internal battery
- Power consumption is <2.5 W, in RTK mode with internal radio
- Average operating times on internal battery:
 - RTK/Static: 5.5 hours³

COMMUNICATIONS AND DATA STORAGE

- Raw GNSS data storage on a 512 Mb Industrial Grade Removable SD Card
- Supports external GSM/GPRS/CDMA modems for point to point RTK
- Supports external and integrated Nomad 800X GPRS modems for NTRIP operations
- Supports external UHF transmit data link for RTK base station operation
 - CMR, RTCM 2.1, RTCM 2.2, RTCM 2.3, RTCM 3.0
- Epoch 35 with integrated internal UHF receive only data link
 - CMR, RTCM 2.3, RTCM 3.0, RTCM 3.1 RTK
 - 410-430 MHz, 430-450MHz, 450-470MHz
 - 25KHz Channel spacing, 4800-9600 bps
 - 12.5KHz Channel spacing, 4800bps

NOTICE TO OUR EUROPEAN UNION CUSTOMERS

For product recycling instructions and more information, please go to www.spectraprecision.com/ev.shtml.

Recycling in Europe:

To recycle Spectra Precision WEEE (Waste Electrical and Electronic Equipment products that run on electrical power), call +31 497 53 24 30, and ask for the "WEEE Associate". Or, mail a request for recycling instructions to: Spectra Precision, c/o Menlo Worldwide Logistics, Meerheide 45, 5521 DZ Eersel, NL.

¹ Accuracy and reliability may be subject to anomalies such as multipath, obstructions, satellite geometry, and atmospheric conditions. Always follow recommended survey practices.

² Depends on WAAS/EGNOS system performance.

³ Two batteries supplied standard.

⁴ Authorized Spectra Precision SD cards only.

Specifications are subject to change without prior notice.



SPECTRA PRECISION
 10355 Westmoor Drive, Suite #100
 Westminster, CO 80021
 USA
 +1-720-587-4700 Phone
 888-477-7516 (Toll Free in USA)
www.spectraprecision.com

www.spectraprecision.com
sales@spectraprecision.com
support@spectraprecision.com