



<b>Angle Measurement</b>	
Horizontal Accuracy (Standard deviation based on DIN 18723)	1" (1.0 mgon)
Vertical Accuracy (Standard deviation based on DIN 18723)	1" (0.6 mgon)
<b>Angle Reading (least count)</b>	
Standard	1" (0.3 mgon)
Tracking	2" (0.6 mgon)
<b>Automatic Level Compensator</b>	Dual-axis compensator +/- 5.4' (+/- 100 mgon)
<b>Distance Measurement Accuracy (Standard Deviation), Prism Mode</b>	
Standard	±(2 mm + 2 ppm) ±(0.0065 ft + 2 ppm)
Tested standard deviation according to ISO17123-4	±(1 mm + 1 ppm) ±(0.003 ft + 1 ppm)
Tracking	±(4 mm + 2 ppm) ±(0.013 ft + 2 ppm)
<b>Dynamic Measurement Capability (Standard Deviation)</b>	
Synchronized Angle and Distance Measurements	Yes
Maximized Position Update Rate	20 Hz
<b>DR Mode</b>	
Standard Measurement	±(2 mm + 2 ppm) ±(0.0065 ft + 2 ppm)
Tracking	±(4 mm + 2 ppm) ±(0.013 ft + 2 ppm)
<b>Measuring Time, Prism Mode</b>	
Standard	1.2 seconds
Tracking	0.4 seconds
<b>Measuring Time, DR Mode</b>	
Standard	1 to 5 seconds
Tracking	0.4 seconds
<b>Range (under clear conditions), Prism Mode</b>	
1 prism	2,500 m (8,202 ft)
1 prism Long Range mode	5,500 m (18,044 ft) max range
3 prism	3500 m (11,482 ft)
Shortest possible range	0.2 m (0.65 ft)
<b>Range (under clear conditions), DR Mode</b>	
Kodak Gray Card (18% reflective)	>600 m (1969 ft)
Kodak Gray Card (90% reflective)	>1300 m (4265 ft)
<b>Range (under difficult conditions), DR Mode</b>	
Kodak Gray Card (18% reflective)	>550 m (1804 ft)
Kodak Gray Card (90% reflective)	>1200 m (3937 ft)
<b>Typical ranges, DR Mode</b>	
Concrete	600 – 800 m (1968 – 2624 ft)
Wood construction	400 – 800 m (1312 – 2624 ft)
Metal construction	400 – 500 m (1312 – 1640 ft)
Light rock	400 – 600 m (1312 – 1968 ft)
Dark rock	300 – 400 m (984 – 1312 ft)
Reflective foil 20 mm x 20 mm (0.7 in x .07 in)	1000 m (3280 ft)
Reflective foil 60 mm x 60 mm (2.3 in x 2.3 in)	1600 m (5,249 ft)
Shortest possible range	1m (6.56 ft)
<b>DR Extended Range Mode</b>	
Kodak Gray Card (18% reflective)	900-1000 m (2952 - 3280 ft)
Kodak Gray Card (90% reflective)	2000 - 2200 m (6560 - 7216 ft)
Accuracy	±(10 mm + 2 ppm) ±(0.033 ft + 2 ppm)
<b>DR surface scan and surface profile speed</b>	3 Hz / 1.3 points per second - turn and measure

# Specifications

# SPS930 DR+ Total Station

<b>Light Source</b>	Pulsed laser diode 905 nm, Laser class 1
<b>Laser pointer coaxial (standard)</b>	Laser class 2
<b>Beam Divergence in Prism Mode</b>	
Horizontal	4 cm/100 m (0.13 ft/328 ft)
Vertical	8 cm/100 m (0.26 ft/328 ft)
<b>Beam Divergence in DR Mode</b>	
Horizontal	
Vertical	
Atmospheric Correction	-130 ppm to 160 ppm continuous
<b>Leveling</b>	
Circular level in Tribrach	8/2 mm (8/0.007 ft)
Electronic 2-axis level in the LCD	0.3" (0.1 mgon)
Servo system	MagDrive servo technology, integrated servo/angle sensor electromagnetic direct drive
Rotation speed	115 degrees/sec (128 gon/sec)
Positioning speed 360/180 degrees (400/200 gon)	3.2 sec / 2.6 sec
Positioning speed - Change Face I to Face II	2.6 sec
Clamps and slow motions	Servo-driven, endless fine adjustment
<b>Centering</b>	
Centering system	Trimble 3-pin
Optical plummet	Alidade optical plummet
Magnification/shortest focusing distance	2.3x/0.5 m – infinity (1.6 ft – infinity)
<b>Telescope</b>	
Magnification	30x
Aperture	40 mm (1.57 inches)
Field of view at 100 m (328 ft)	2.6 m at 100 m (8.5 ft at 328 ft)
Shortest focusing distance	1.5 m (4.92 ft)–infinity
Illuminated crosshair	Variable (10 steps)
Built-in tracklight	Standard
Operating temperature	-20 °C to +50 °C (-4 °F to +122 °F)
Dust and water proofing	IP55
Focus type	Servo assisted on side cover and autofocus
<b>Power Supply</b>	
Internal battery	Rechargeable Li-Ion battery 11.1 V, 4.4 Ah
<b>Operating Time</b>	
One internal battery	Approximately 6 hours
Three internal batteries in multi-battery adaptor	Approximately 18 hours
Robotic holder with one internal battery	Approximately 12 hours
<b>Weight</b>	
Instrument (Servo/Autolock)	5.15 kg (11.35 lb)
Instrument (Robotic)	5.25 kg (11.57 lb)
Trimble CU Controller	0.4 kg (0.88 lb)
Tribrach	0.7 kg (1.54 lb)
Internal battery	0.35 kg (0.77 lb)
	196 mm (7.71 in)
<b>Trunnion axis Height</b>	
<b>Handle</b>	Detachable and eccentric for unrestricted sighting
<b>Range</b>	
Robotic	500–700 m (1,640–2,297 ft)
Autolock	500–700 m (1,640–2,297 ft)
Autolock to Trimble MT1000 Target	800 m (2625 ft)
Shortest search distance	0.2 m (.65 ft)
Autolock pointing precision at 200 m (656 ft) (Standard deviation)	<2 mm (0.007 ft)
<b>Angle Reading</b>	
Standard	1" (0.3 mgon)
Tracking	2" (0.6 mgon)
Averaged observations	0.1" (0.03 mgon)
Type of radio	2.4 GHz frequency-hopping, spread-spectrum radios
Search time	2 – 10 s
Search area	360 degrees (400 gon) or defined horizontal and vertical search window
<b>Communication</b>	USB, Serial, Bluetooth®

# Specifications

# SPS930 DR+ Total Station

## Machine Control Specifications

Machine Control Capable  
Range to target (MT900)

Optional  
5m – 500-700 m, from 2m with reduced performance

Search time  
Search area  
Maximum acceleration of target at short distance 2 m  
(6.5 ft) radial acceleration

2 to 10 seconds  
360 degrees (400 gon) or defined horizontal and vertical search window  
148%/sec

## Maximum velocity of target

Radial speed  
Axial speed

114%/sec  
6m/s

## Data Output

Rate  
Data Timing  
Data Latency  
Synchronized measurement data

20 Hz  
+/- 1 ms  
40 ms over Cirronet radio, 23 ms over USB connection  
<1 ms

## Accuracy to a target moving at 1 m/s (Standard deviation)

Horizontal  
Vertical  
Slope Distance

$\pm (2 \text{ mm} + 14 \text{ ppm}) \pm (0.007 \text{ ft} + 14 \text{ ppm})$   
 $\pm (2 \text{ mm} + 14 \text{ ppm}) \pm (0.007 \text{ ft} + 14 \text{ ppm})$   
 $\pm (2 \text{ mm} + 14 \text{ ppm}) \pm (0.007 \text{ ft} + 14 \text{ ppm})$

## Models Available

Servo, Autolock, Robotic. UTS

## Upgradable

Yes

*Specifications subject to change without notice.*

*© 2010, Trimble Navigation Limited. All rights reserved. Trimble, and the Globe & Triangle logo are trademarks of Trimble Navigation Limited, registered in the United States and in other countries. All other trademarks are the property of their respective owners. PN 022482-1535*

## Trimble Heavy and Highway Business Area

5475 Kellenburger Road  
Dayton, Ohio 45424  
USA  
800-538-7800 (Toll Free)  
+1-937-245-5154 Phone  
+1-937-233-9441 Fax  
[www.trimble.com](http://www.trimble.com)

## Trimble Authorized Distribution Partner