

Specifications

Trimble Zephyr Model 2 Geodetic Antenna



Trimble Zephyr™ Model 2 Geodetic Antenna

L1/L2/L5/G1/G2/OmniSTAR/SBAS/E1/E2/E5ab/E6

Frequencies	
Dimensions	dia 34.3 cm x 7.9 cm H (dia 13.5" x 3.1" H)
Weight	1.36 kgs (3.0 lbs)
Antenna cable connector	TNC. Sealed
Mounting	5/8"-11 UNC thread mount
Operation temperature	-40 °C to +70 °C (-40 °F to 158 °F)
Storage temperature	-55 °C to +85 °C (-67 °F to 185 °F)
Environmental	MIL-810-F Figure 514.5c-17 vibration levels on each axis Shock tested table MIL-810-F Table 516.5-I 2m drop, bouyant
Humidity	100% humidity proof, fully sealed
Feed	4 point
LNA(Low Noise Amplifier) input	3.3 V DC – 12 V DC (100 mA)
LNA(Low Noise Amplifier) gain	L1 50dB / L2 50dB
Antenna compliance	CE
Phase stability	<2 mm

Specifications subject to change without notice.

© 2008, Trimble Navigation Limited. All rights reserved. Trimble, and the Globe & Triangle logo are trademarks of Trimble Navigation Limited, registered in the United States and in other countries. Zephyr is a trademark of Trimble Navigation Limited. All other trademarks are the property of their respective owners. PN 022482-1496.

Trimble Heavy and Highway Business Area

5475 Kellenburger Road
Dayton, Ohio 45424
USA
800-538-7800 (Toll Free)
+1-937-245-5154 Phone
+1-937-233-9441 Fax
www.trimble.com

Trimble Authorized Distribution Partner